


Micro Optimo

Adjustable Picture Mount

| | |
|----------|--|
| Type: | |
| Project: | |



DIMENSIONS



ORDERING LOGIC

| MBEAMDI | - | - | - | - | - |
|---------|---|------------------|---|----------------------|---------------------|
| SERIES | - | LENGTH | - | DIRECT LUMENS PER FT | - |
| MOPTD | - | 4=4FT | - | 350=350LPF | SD=Satinice Diffuse |
| | - | 8=8FT | - | 500=500LPF | |
| | - | XX=Custom Length | - | 775=775LPF | |
| | - | | - | 1000=1000LPF | |
| | | | | XX=Custom LPF | |
| | | | | | CCT (80+ CRI) |
| | | | | | 30K=3000K |
| | | | | | 35K=3500K |
| | | | | | 40K=4000K |
| | | | | | 50K=5000K |

| - | - | - | - |
|---|---------------------------------|-------------------------|---|
| FINISH | MOUNTING | VOLTAGE | OPTIONS |
| PW=Powder Coat White PB=Powder Coat Black PS=Powder Coat Silver PBR=Powder Coat Bronze PSFx=Premium Stock Finish (See Pg. ?) PO=Powder Coat Other* *Factory to be supplied with RAL# or color chip | RWM = (Rotational Wall Mount) | U= 120v-277v C= 347v | CRI9050=Minimum 90+ CRI (R9 - 50) DD=Dual Drivers #EMB10=10W EM Battery |

EXAMPLE: **MOPTD-4-775-SD-35K-PB-PCB-U-CRI9050**

FEATURES

- Soft diffused direct illumination in a sleek modern minimalist style.
- Thermally efficient extruded aluminum single piece housing
- 4' and 8' individual units, or custom lengths
- Toolless height adjustment at the ceiling
- Textured powder coat finishes available in white, black, silver and bronze
- Premium finishes also available
- Approved for dry and damp locations
- 0-10v dimming is standard
- Dim to 1% of output current is standard
- Three choices of remote drivers, surface mount, in-wall or powered ceiling canopy.



LUMEN PACKAGES

Based on 3500K CCT. Other CCT available.
NOTE: Lumen Package total cannot exceed 12,000 unless a "DD" (Dual Driver) option is selected

| MODEL | LUMENS | INPUT WATTS | Lm/W |
|---------------------|--------|-------------|------|
| MOPTD-4-1000-SD-35K | 4,000 | 39 | 104 |
| MOPTD-8-1000-SD-35K | 8,000 | 77 | 104 |