




















		LEGEND																											
		 Standard Option																											
		 Non-standard Option																											
Mounting Method		Light Direction			Shielding					Distribution								Standard Lumen Range (lm/ft)		Design Options									
Features											Direct					Indirect				Consult factory for extended performance.									
		Direct Only	Indirect Only	Direct/Indirect	Flush	Regress	Direct Drop .5"	Direct Drop 1"	Direct Drop 1.5"	Direct Drop Lit Ends	Lambertian	Batwing	Wall Wash	Room Fill	Grazer	Lambertian	Batwing	Room Fill	Grazer			Continuous Runs - 6" Increments	Continuous Runs - 1/16" Increments	Patterns	Custom Finishes	Remote Power Box	Emergency Battery	Control Solutions	Damp Location
BEAM	Surface	★			★		★	★	★	★	★	★	★							Min. 100 Direct/ 100 Indirect Max. 1400 Direct/ 1400 Indirect	★	●	★	★	●	★	★	★	
	Suspended	★		★	★		★	★	★	★	★	★	★		★	★					★	●	★	★	●	★	★	★	
	Wall	★		★	★		★	★	★	★	★	★	★		★	★					★	●	★	★	●	★	★	★	
	Recessed Drywall	★			★		★	★	★	★	★	★	★								★	★	★	★	●	★	★	★	
	Recessed Grid	★			★	★	★	★	★	★	★	★	★								★	★	★	★	●	★	★	★	
	Perimeter	★			★	★					★			★							★	★	★	★	●	★	★	★	
SLIM BEAM	Surface	★			★		★	★	★	★	★	★	★							Min. 100 Direct/ 100 Indirect Max. 1400 Direct/ 1400 Indirect	★	●	★	★	●	★	★	★	
	Suspended	★	★	★	★		★	★	★	★	★	★	★		★	★					★	●	★	★	●	★	★	★	
	Wall	★	★	★	★		★	★	★	★	★	★	★		★	★					★	●	★	★	●	★	★	★	
	Recessed Drywall	★			★		★	★	★	★	★	★	★								★	★	★	★	●	★	★	★	
	Recessed Grid	★			★	★	★	★	★	★	★	★	★								★	★	★	★	●	★	★	★	
	Perimeter	★			★	★					★			★	★						★	★	★	★	●	★	★	★	
TALL BEAM	Suspended	★		★	★						★	★	★			★	★			Min. 100 Direct/ 100 Indirect Max. 1400 Direct/ 1400 Indirect	★	●	★	★	●	★	★	★	
Wall	★		★	★						★	★	★			★	★			★		●	★	★	●	★	★	★		
X-BEAM	Suspended	★		★		★					★	★				★	★				★			★	●	★	★		
CLOVER BEAM	Surface	★			★						★	★	★								★	●		★	●	★	★	★	
	Suspended	★		★	★						★	★	★			★	★				★	●		★	●	★	★	★	
SCULPTURA	Surface	★			★						★									Min. 100 Direct/ 100 Indirect Max. 1400 Direct/ 1400 Indirect			★	★	●	★	★	★	
	Suspended	★		★	★						★					★	★						★	★	●	★	★	★	
	Wall	★		★	★						★					★	★						★	★	●	★	★	★	
	Recessed Drywall	★			★						★													★	●	★	★	★	
	Recessed Grid	★			★						★													★	●	★	★	★	

★

Standard Option

●

Non-standard Option