


| | |
|------------|--|
| Type: | |
| Project: | |
| REP/Agent: | |
| Order #: | |


SLIM BEAM DIRECT/INDIRECT




DIFFUSING




FLUSH, H: 3.5"



DL05, H: 4.0"



DL10, H: 4.5"




DL15, H: 5.0"


FEATURES

- ★ Continuous lensing standard—runs up to 200'
- ★ Extruded aluminum single piece housing
- ★ Standard 2', 4', 6' and 8' units, or continuous rows
- ★ Linear runs with proprietary joiner design
- ★ Direct & indirect light levels can be set to any combination at the factory
- ★ Efficacy up to 140 lm/W
- ★ Soft diffuse direct lighting
- ★ Textured powder coat finishes available in white, black and silver
- ★ Premium finishes also available
- ★ Approved for dry and damp locations
- ★ 0-10v dimming is standard
- ★ Dim to 1% of output current is standard
- ★ 90 CRI (R9 50min) available
- ★ CA Title 24 / JA8 installation compatible
- ★ Consult factory for TM21, TM30, LM79 and LM80


DIMENSIONS



DISTRIBUTION



Direct: SD= Satinice Diffuse
Indirect: CL= Clear



Direct: WD= Wide Diffuse
Indirect: BW= Batwing



Declare.

| | |
|------------|--|
| Type: | |
| Project: | |
| REP/Agent: | |
| Order #: | |

SLIM BEAM DIRECT/INDIRECT

| SLIMDI | | | | | |
|--------|---------------------------|------------------------|--------------------------|---|-----------------------|
| SERIES | LENGTH | DIRECT LUMENS PER FOOT | INDIRECT LUMENS PER FOOT | DIRECT DISTRIBUTION | INDIRECT DISTRIBUTION |
| SLIMDI | xx= Run Length | 350= 350 LPF | 350= 350 LPF | SD= Satinice Diffuse | CL= Clear Lens |
| | Sxx= Symmetric Run Length | 500= 500 LPF | 500= 500 LPF | WD= Wide Diffuse | BW= Batwing |
| | _x_RECT= Rectangle | 750= 750 LPF | 750= 750 LPF | WW= Wall Wash | |
| | _x_L= L-Shape | 1000=1000 LPF | 1000= 1000 LPF | DL05= Satin Diffuse 0.5" Drop | |
| | _x_x_U= U-Shape | XXX= Custom LPF | XXX= Custom LPF | DL10= Satin Diffuse 1.0" Drop | |
| | | | | DL15= Satin Diffuse 1.5" Drop | |
| | | | | DLLE05= 0.5" Drop w/ Lit Ends | |
| | | | | DLLE10= 1.0" Drop w/ Lit Ends | |
| | | | | DLLE15= 1.5" Drop w/ Lit Ends | |
| | | | | Seamless Continuous Lensing Unavailable for "DL" Options. | |

| CCT | CRI | FINISH | MOUNTING | VOLTAGE | ELECTRICAL |
|--|--------------------|---|--------------------------------|------------|---|
| 30K= 3000K | 80= 80 | <u>STANDARD</u> | <u>CABLES WITH CANOPY KITS</u> | U= 120-277 | 1C= Single Circuit |
| 35K= 3500K | 90= 90 (R9 50 min) | PW= Powder Coat White | ACW05= White Cord 5' | C= 347 | 2C= Separate D/I Circuits |
| 40K= 4000K | | PB= Powder Coat Black | ACW10= White Cord 10' | | (separate control of direct and indirect) |
| 50K= 5000K | | PS= Powder Coat Silver | ACB05= Black Cord 5' | | MC= Multiple Circuits |
| TW= Tunable white ¹ (2700-6500K) | | | ACB10= Black Cord 10' | | (multiple switch legs across run length) |
| | | <u>PREMIUM</u> | <u>CABLES WITH LOOPS</u> | | EC= Emergency Circuit |
| | | RALxxxx= Powder Coat RAL xxxx (Gloss Finish) | ALW10= White Cord 10' | | (separate power drops for EC fixtures) |
| | | PSFx= Prem Stock Finish | ALB10= Black Cord 10' | | GTD= Generator Transfer Device |
| | | <u>CUSTOM</u> | <u>WALL MOUNTS</u> | | |
| | | PO= Powder Other | WM= Wall Mount | | |
| | | See pg.8 for standard and premium options. | AWM= Architectural Wall Mt | | |
| | | | EWM= Extruded Wall Mount | | |
| | | | <u>STEM WITH CANOPY KITS</u> | | |
| | | | STEMWxx= Stem White, xx" | | |
| | | | STEMBxx= Stem Black, xx" | | |

| OPTIONS |
|---------|
|---------|

SPECIALTY DRIVERS (Standard driver is 0-10V, dim to 1% output current)

DT1=eldoLED EcoDrive Dim to 1% (0-10V)
 DTZ=eldoLED SoloDrive Dim to 0.1% (0-10V)
 PSRD=Philips Sensor Ready (DALI) Driver
 LDE1=Lutron Hi-Lume EcoSystem LED driver with Soft-on, Fade-to-Black
 TW-A=Tunable White, 0-10v²
 TW-EL=eldoLED DUALdrive Tunable White (DALI)²
 PSQ02U=Lutron T-Series 1% 2-Channel Tunable White driver²

SENSORS

DMxx%=Daylight/Motion Sensor (xx% = % Min. Dimming)
 VDO=Lutron Vive Integral fixture control (RF w/ daylight and occupancy)
 AWNR-W= Lutron Athena Wireless Node (RF only)³ - White Finish
 AWNR-B= Lutron Athena Wireless Node (RF only)³ - Black Finish

ENDCAPS

RD = round endcap (not available with "DL" options)

BATTERIES

#EMB6=6W EM Battery (Bodine BSL06T3)
 #EMB10=10W EM Battery (Bodine BSL10T3)
 #FCEMB10= 10W EM Battery (Factory Choice)
 #FCEMB14= 14W EM Battery (Factory Choice)

EXAMPLE: **SLIMDI-40-500-750-WD-BW-35K-90-PW-ACW10-U-1C-1EMB10**


¹ Tunable White Driver must be specified in options

² 50 Watt Max. Dual driver required for higher fixture wattage


³ D4i driver for static & DALI-2 Type 8 for tunable.

MOUNTING OPTIONS


ACxxx (Aircraft Cable with Canopy) - Drywall, Solid, Tile (On-Grid), Tile (Off-Grid)




ALxxx (Aircraft Cable with Loops)




POWER CORD & FIRST MOUNT DETAIL



WM (Wall Mount)






AWM (Architectural Wall Mount)





MOUNTING OPTIONS, CONTINUED

EWM (Extruded Wall Mount)



STEMWxx, STEMBxx (Stem Mount)



ROW CONFIGURATIONS

xx (Run Length)

The standard construction of run lengths follows the logic of the table below. Consult factory for additional information.

| # of Sections | Total Length | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------------|--------------|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 |
| 2 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | | | 1 | | | | | 1 | 1 | 1 | 1 | | | | | 1 | 1 | 1 | 1 | | | | | 1 | 1 | 1 | 1 | | | | 1 | 1 | 1 | 1 | | | | | |
| 5 | | | | 1 | | | | 1 | | | 1 | | | | 1 | | | | 1 | | | | | 1 | | | | 1 | | | 1 | | | | | 1 | | | |
| 6 | | | | | 1 | | | | 1 | | | | 1 | | | | 1 | | | | 1 | | | | 1 | | | | 1 | | | 1 | | | | | 1 | | |
| 7 | | | | | | 1 | | | | 1 | | | | 1 | | | | 1 | | | | 1 | | | | 1 | | | 1 | | | 1 | | | | | 1 | | |
| 8 | | | | | | 1 | | | | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 2 | 2 | 2 | 2 | 3 | 2 | 2 | 2 | 3 | 3 | 3 | 3 | 4 | 3 | 3 | 3 | 4 | 4 | 4 | 4 | 5 | |

NOTE: Fixtures in continuous runs are available in 6" increments. Consult factory for smaller increments.

Sxx (Symmetric Run)

The construction of Sxx (y') is to build with equal length fixtures. The xx indicates the run length. The y' indicates the fixture length used to create the run. Please indicate this on your P.O. when placing your order.

| | | | | | |
|-------------------|----|----|----|----|----|
| \$12' (2') | 2' | 2' | 2' | 2' | 2' |
| \$12' (3') | 3' | 3' | 3' | 3' | 3' |
| \$12' (4') | 4' | 4' | 4' | 4' | 4' |
| \$12' (6') | 6' | 6' | 6' | 6' | 6' |

MOUNTING LOCATIONS


Each starter or individual fixture will be provided with (2) mounting supports (●). Each additional fixture will be provided with (1) support which can be located anywhere along the 2nd half of the fixture (highlighted below):

Examples of continuous run mounting locations are as follows:

| | | | | | |
|----------------|---|----|---|----|-------|
| 12' RUN | ● | 8' | ● | 4' | |
| 16' RUN | ● | 8' | ● | 8' | |
| 20' RUN | ● | 8' | ● | 8' | 4' |
| 24' RUN | ● | 8' | ● | 8' | 8' |
| 28' RUN | ● | 8' | ● | 8' | 8' 4' |

JOINT SHAPE CONFIGURATION WITH MITER CUTS




We provide joint configurations in the stock size of 24" X 24" as shown below.



| |
|-----------------------|
| _x_RECT |
| Rectangle |
| Supply AxB dimensions |

| |
|-----------------------|
| _x_L |
| L-Shape |
| Supply AxB dimensions |

| |
|-------------------------|
| _x_x_U |
| U-Shape |
| Supply AxBxC dimensions |




ENDCAP OPTIONS



RD, H: 3.5"

PERFORMANCE


SLIMDI-X-325-750-WD-BW (80+ CRI)



| Model | Lumens | Watts | LPW |
|----------------------------|--------|-------|-----|
| SLIMDI-4-325-750-WD-BW-30K | 4300 | 37 | 116 |
| SLIMDI-4-325-750-WD-BW-35K | 4300 | 36 | 120 |
| SLIMDI-4-325-750-WD-BW-40K | 4300 | 35 | 124 |
| SLIMDI-4-325-750-WD-BW-50K | 4300 | 34 | 126 |

| Model | Lumens | Watts | LPW |
|----------------------------|--------|-------|-----|
| SLIMDI-8-325-750-WD-BW-30K | 8600 | 72 | 119 |
| SLIMDI-8-325-750-WD-BW-35K | 8600 | 71 | 121 |
| SLIMDI-8-325-750-WD-BW-40K | 8600 | 68 | 127 |
| SLIMDI-8-325-750-WD-BW-50K | 8600 | 67 | 128 |

SLIMDI-X-400-375-SD-CL (80+ CRI)




| Model | Lumens | Watts | LPW |
|----------------------------|--------|-------|-----|
| SLIMDI-4-400-375-SD-CL-30K | 3,025 | 25 | 122 |
| SLIMDI-4-400-375-SD-CL-35K | 3,025 | 24 | 128 |
| SLIMDI-4-400-375-SD-CL-40K | 3,025 | 23 | 132 |
| SLIMDI-4-400-375-SD-CL-50K | 3,025 | 23 | 134 |


| Model | Lumens | Watts | LPW |
|----------------------------|--------|-------|-----|
| SLIMDI-8-400-375-SD-CL-30K | 6,050 | 47 | 128 |
| SLIMDI-8-400-375-SD-CL-35K | 6,050 | 45 | 134 |
| SLIMDI-8-400-375-SD-CL-40K | 6,050 | 44 | 138 |
| SLIMDI-8-400-375-SD-CL-50K | 6,050 | 43 | 141 |

LENS OPTIONS


FLUSH



STANDARD DROP LENS



DROP LENS w/ LIT ENDS




FINISHES


STANDARD FINISHES



WHITE MINI TEXTURE



BLACK MINI TEXTURE




SILVER SPARKLE TEXTURE

PREMIUM STOCK FINISHES



PSF001 (WOOD#1)



PSF002 (WOOD#2)



PSF003 (WOOD#3)




PSF004 (WOOD#4)



PSF005 (WOOD#5)



PSF006 (WOOD#6)



PSF007 (STONE #1)



PSF008 (STONE #2)



PSF009 (METAL #1)

NOTE: A minimal impact to lead times will apply to products specified with Premium Stock Finishes (PSF). It is not to be assumed that these finishes are stocked in our warehouse, but rather, are readily available to us for your project.

All other custom finishes (PO) will incur a set up fee and will add an extended lead time to your project.

SPECIFICATIONS

Housing

Nominal 2" x 3.5" x .075" thick housing of continuous extruded 6063 T5 aluminum.

Color

Colors for the housing are available in a powder coated white, black, silver, and woodgrain with end cap to match. Consult factory for custom colors.

Luminaire Length

2', 4', 6' or 8' lengths are available for a single stand-alone section. Using internal joiners, these sections can be joined to form longer rows.

End Caps

Injection molded flat end caps are mechanically attached with no exposed fasteners to enhance architectural aesthetic and prevent light leak.

Source

Lumen packages are available in four color temperature options (3000K, 3500K, 4000K and 5000K) — all within 3 MacAdam ellipses.

Certification

Intertek cETLus Listed. RoHS (Restriction of Hazardous Substances) and Buy American Act compliant.

Battery

Philips Bodine lithium ion battery providing up to 780lm(6W) or up to 1300lm(10W) for 90 minutes. UL924 listed. Class 2 compliant. Meets Title 20 CEC (California Energy Commission) efficiency standards.

Environment

Suitable for dry and damp locations.

Operating temp.: -40°C to +50°C

-40°F to +122°F

Dimming Driver (Integral Driver)

Constant current programmable LED driver, UL listed, class P, 0-10V, dim to 1% of output current. 2.5KV ring wave surge protection and >.90 power factor.


Packaging

Sustainably manufactured outside cardboard box and biodegradable, protective poly-foam luminaire inserts.

CONTROL

Sensor

Wattstopper FS-205 v2 Low Voltage PIR. Integrated photosensor for hold-off daylighting control. 24VDC operating voltage. Adjustable time delay (30 seconds to 30 minutes).



Wireless Node



WARRANTY

5-year limited warranty. Complete warranty terms can be located at:

http://www.starteklightingamerica.com/images/pdf/warranty/Beam_Series_Warranty.pdf

Note: Actual performance may differ as a result of installation environment and final application.

All values are design or typical values, measured under laboratory conditions, at 25°C (77°F).

COMPANION PRODUCTS

Slim Beam Direct



Slim Beam Surface Mount



Recessed Slim Beam

