



Type:	
Project:	
REP/Agent:	
Order #:	

MICRO BEAM DIRECT




DIMENSIONS



FEATURES

- ★ Soft diffused direct illumination in a sleek modern minimalist style.
- ★ Thermally efficient extruded aluminum single piece housing
- ★ 4' and 8' individual units, or custom lengths
- ★ Toolless height adjustment at the ceiling
- ★ Efficacy up to 115 lm/W
- ★ Textured powder coat finishes available in white, black, and silver
- ★ Premium finishes also available
- ★ Approved for dry and damp locations
- ★ 0-10v dimming is standard
- ★ Dim to 1% of output current is standard
- ★ 90 CRI (R9 50 min) available
- ★ 5 year system warranty
- ★ Class 2 input for luminaire
- ★ Three power choices of Hyperdrive remote power system

DISTRIBUTION



WD= Wide Diffuse

LUMEN PACKAGES

Based on 3500K CCT. Other CCT available.

MODEL	LUMENS	INPUT WATTS	Lm/W
MBEAMD-4-750-SD-35K-80	3000	34	98
MBEAMD-8-750-SD-35K-80	6000	54	110





MICRO BEAM DIRECT

Type:	
Project:	
REP/Agent:	
Order #:	

MBEAMD					
Series	Length	Lumens per Foot	Distribution	CCT	CRI
MBEAMD	4= 4FT 8= 8FT xx= Custom length Sxx= Symmetric Run Length _x_RECT= Rectangle _x_L= L-Shape _x_H= Hexagon _x_x_U= U-Shape	350= 350 LPF 500= 500 LPF 750= 750 LPF 1000= 1000 LPF xx= Custom LPF	SD= Satinice Diffuse WD= Wide Diffuse	30K= 3000K 35K= 3500K 40K= 4000K 50K= 5000K	80= 80 90= 90 (R9 50 min)

FINISH	MOUNTING (See Page 6-8 for Options)	ELECTRICAL
STANDARD PW= Powder Coat White PB= Powder Coat Black PS= Powder Coat Silver	POWERED CANOPY (Driver included, 120-277V) ³ PCW= Powered Canopy White PCB= Powered Canopy Black	1C= Single Circuit
PREMIUM PSFx= Premium Stock Finish	CANOPY RECESSED CRW= Canopy Recessed White CRB= Canopy Recessed Black	
CUSTOM PO= Powder Coat Other*	CANOPY T-GRID CTW= Canopy T-Grid White CTB= Canopy T-Grid Black	
See pg. 10 for standard and premium options.	CANOPY SURFACE CSW= Canopy Surface White CSB= Canopy Surface Black	*Items in grey box require Hyperdrive Remote Driver*

REMOTE OPTIONS	HYPERDRIVE CIRCUIT
Ex = EM Battery designated fixture (Ordered with Hyperdrive) Replace X with battery Qty. Not available with Powered Canopy, Consult factory	HDxx = HyperDrive Circuit Not required for the Powered Canopy configuration

EXAMPLE: MBEAM-4-750-SD-35K-80-PW-CSW-HD01

¹ Requires Hyperdrive Remote Driver
² Tunable White Driver must be specified
³ 50W Max. Dual driver required

Type:	
Project:	
REP/Agent:	
Order #:	

HYPD HYPER DRIVE REMOTE POWER SYSTEM

HYPD				
SERIES	SIZE / DRIVER QTY	EMERGENCY BATTERY (OPTIONAL)	MOUNTING	FINISH
HYPD	Replace x with driver quantity Sx = Small- up to two drivers (190W) Mx = Medium- up to four drivers (300W) Lx = Large- up to eight drivers (600W)	Replace # with battery quantity NB = No Emergency Battery #EMB6 = 6W EM Battery (Iota/Bodine) #EMB10 = 10W EM Battery (Iota/Bodine) #FCEMB10 = 10W EM Battery (Factory Choice)	S = Surface/ Strut R = Recessed	STANDARD PW = Powder Coat White PB = Powder Coat Black
		PREMIUM RALxxxx = Power Coat RAL xxxx (Gloss Finish)		
		<i>Note: Batteries are only available in Medium and Large enclosures. Each emergency battery reduces the driver quantity of the Hyper Drive.</i>		
VOLTAGE	OPTIONS	HYPERDRIVE CIRCUIT		
U= 120-277	SPECIALTY DRIVERS <i>(Standard driver is 0-10V, dim to 1% output current)</i> DT1 = eldoLED EcoDrive Dim to 1% (0-10V) DTZ = eldoLED SoloDrive Dim to 0.1% (0-10V) PSRD = Signify Sensor Ready (DALI) Driver LDE1 = Lutron Hi-Lume EcoSystem LED driver w/ Soft-on, Fade-to-Black TW-A = Tunable White, 0-10v TW-EL = eldoLED DUALdrive Tunable White (DALI) Consult factory for additional driver options <i>Note: Specialty driver options are not available with the small power-box option, with the exception of TW-A</i>	HDxx = HyperDrive Circuit		
	SENSORS Consult factory for options			
	OTHERS CP = Chicago Plenum (CCEA)			


EXAMPLE: HYPD-L8-NB-R-PW-DTZ-HD01

NOTES & LIMITATIONS

Consult factory for custom configurations and drivers not listed.

L8 configuration shown (shown with front cover removed)


Each driver is provided with a terminal block on both input and output side for ease of wiring and installation.




HYPERRIVE REMOTE POWER SYSTEM

Sx (Small Hyper Drive Remote Canopy)

Surface Mount




Recessed Mount




Driver Form Factor	Compact
Input Rating	120-277V
Outputs	Up to 2 (190W max)
Max Remote Distance	Up to 100' (30.5m)
Knockouts	(9) 1/2"
Battery	Not Available

Mx (Medium Hyper Drive Remote Canopy)

Surface Mount




Recessed Mount




Driver Form Factor	Linear
Input Rating	120-277V
Outputs	Up to 4 (300W max)
Max Remote Distance	Up to 100' (30.5m)
Knockouts	(20) 1/2"
Battery	Available

Lx (Large Hyper Drive Remote Canopy)

Surface Mount



Recessed Mount



Driver Form Factor	Linear
Input Rating	120-277V
Outputs	Up to 8 (600W max)
Max Remote Distance	Up to 100' (30.5m)
Knockouts	(20) 1/2"
Battery	Available

How to use this guide

Fill out the worksheet to specify your requirements for your configurations.
Be sure to callout battery and sensor locations.

Refer to the run chart for standard run configurations on linear lengths,
consult factory for custom configurations.

Use the order guide to create your BOM for your configuration.


Submit the worksheet along with your order.

#1 Example Bill of Materials

Qty. Type

3	MBEAMD-8-750-SD-35K-80-PW-CSW-HD01	
3	MBEAMD-4-750-SD-35K-80-PW-CSW-HD01	
1	HYPD-L6-NB-R-PW-DTZ-HD01	

#1 Example Configuration




Note: Low Voltage Power transfer wire between fixture and HyperDrive remote power system provided by others.

#2 Example Bill of Materials

Qty. Type

3	MBEAMD-8-750-SD-35K-80-PW-CSW-HD01	
2	MBEAMD-6-750-SD-35K-80-PW-CSW-HD01	
1	MBEAMD-2-750-SD-35K-80-PW-CSW-HD01	
1	MBEAMD-10-750-SD-35K-80-PW-CSW-HD01	
1	MBEAMD-6-750-SD-35K-80-PW-CSW-E1-HD02	
1	MBEAMD-10-750-SD-35K-80-PW-CSW-HD02	
1	HYPD-L8-NB-R-PW-DTZ-HD01	
1	HYPD-M3-1EMB6-R-PW-DTZ-HD02	

#2 Example Configuration




Note: Low Voltage Power transfer wire between fixture and HyperDrive remote power system provided by others.

MOUNTING OPTIONS


2' - 6' Fixtures require 1 Non-Feed Mount. Fixtures larger than 6' require 2 Non-Feed Mount.

PCx - Powered Canopy (Driver Included)

Power Feed




Non-Feed




CRx - Canopy Recessed

Power Feed




Non-Feed




**REQUIRES
HYPERDRIVE**

CTx - Canopy T-Grid

Power Feed




Non-Feed




REQUIRES
HYPERDRIVE

CSx - Canopy Surface

Power Feed




Non-Feed




REQUIRES
HYPERDRIVE

We provide joint configurations in the various shapes shown below.



90 Degree Corner Hub






60 Degree Corner Hub

_x_RECT
Rectangle
Supply AxB dimensions


_x_L
L-Shape
Supply AxB dimensions

_x_x_U
U-Shape
Supply AxB dimensions



_x_H
Hexagon
Supply AxB dimensions


● = Power Location



STANDARD FINISHES



WHITE MINI TEXTURE



BLACK MINI TEXTURE



SILVER SPARKLE TEXTURE

PREMIUM STOCK FINISHES



PSF001 (WOOD#1)



PSF002 (WOOD#2)



PSF003 (WOOD#3)



PSF004 (WOOD#4)



PSF005 (WOOD#5)



PSF006 (WOOD#6)



PSF007 (STONE #1)



PSF008 (STONE #2)



PSF009 (METAL #1)

NOTE: A minimal impact to lead times will apply to products specified with Premium Stock Finishes (PSF). It is not to be assumed that these finishes are stocked in our warehouse, but rather, are readily available to us for your project.

All other custom finishes (PO) will incur a set up fee and will add an extended lead time to your project.

SPECIFICATIONS

Housing

Nominal 1 1/4" x 1 1/4" square housing of continuous extruded 6063 T5 aluminum.

Color

Colors for the housing are available in a powder coated white, black, silver and woodgrain with end cap to match. Consult factory for custom colors.

Luminaire Length

4' or 8' lengths are available for a single stand-alone section.

End Caps

Machined Aluminum flat end caps are mechanically attached with no exposed fasteners to enhance architectural aesthetic and prevent light leak.

Source

Lumen packages are available in four color temperature options (3000K, 3500K, 4000K and 5000K) — all within 3 MacAdam ellipses.

Certification

RoHS (Restriction of Hazardous Substances) and Buy American Act compliant.

Battery

Lithium battery providing up to 780lm(6W) or up to 1300lm(10W) for 90 minutes. UL924 listed. Class 2 compliant. Meets Title 20 CEC (California Energy Commission) efficiency standards. Requires Hyperdrive medium or large as well as Test/ Status switch is located on "HyperDrive"

Environment

Suitable for dry and damp locations.

Operating temp.: -40°C to +50°C
-40°F to +122°F

Dimming Driver

UL listed, class P (0-10V) dimming driver with programmable current for configurable fixture lumen outputs.

2.5 Kv overcurrent protection


Power factor >.9

Packaging

Sustainably manufactured outside cardboard box and biodegradable, protective poly-foam luminaire inserts.

COMPANION PRODUCTS

Micro Beam Direct/Indirect



WARRANTY

5-year limited warranty. Complete warranty terms can be located at:

http://www.starteklightingamerica.com/images/pdf/warranty/Beam_Series_Warranty.pdf

Note: Actual performance may differ as a result of installation environment and final application.
All values are design or typical values, measured under laboratory conditions, at 25°C (77°F).