


Type:	
Project:	
REP/Agent:	
Order #:	


TALL BEAM DIRECT/INDIRECT




DIMENSIONS



DISTRIBUTION



Direct: SD= Satinice Diffuse
Indirect: CL= Clear



Direct: WD= Wide Diffuse
Indirect: BW= Batwing

FEATURES

- ★ Continuous lensing standard— runs up to 200'
- ★ Extruded aluminum single piece housing
- ★ Standard 2', 4', 6' and 8' units, or continuous rows
- ★ Linear runs with proprietary joiner design
- ★ Direct & Indirect light levels can be set to any combination at the factory
- ★ Efficacy up to 140 lm/W
- ★ Soft diffuse direct lighting
- ★ Textured powder coat finishes available in white, black, and silver
- ★ Premium finishes also available
- ★ Approved for dry and damp locations
- ★ 0-10v dimming is standard
- ★ Dim to 1% of output current is standard
- ★ 90 CRI (R9 50min) available
- ★ CA Title 24 / JA8 installation compatible
- ★ Consult factory for TM21, TM30, LM79 and LM80

LUMEN PACKAGES

Based on 3500K CCT. Other CCT available.

MODEL	LUMENS	INPUT WATTS	LM/W
TALLDI-4-325-750-WD-BW-35K-80	4300	36	120
TALLDI-8-325-750-WD-BW-35K-80	8600	71	121



Declare.

Type:	
Project:	
REP/Agent:	
Order #:	

TALL BEAM DIRECT/INDIRECT

TALLDI					
SERIES	LENGTH	DIRECT LUMENS PER FOOT	INDIRECT LUMENS PER FOOT	DIRECT DISTRIBUTION	INDIRECT DISTRIBUTION
TALLDI	xx= Run Length	350= 350 LPF	350= 350 LPF	SD= Satinice Diffuse	CL= Clear Lens
	Sxx= Symmetric Run Length	500= 500 LPF	500= 500 LPF	WD= Wide Diffuse	BW= Batwing
	_x_RECT= Rectangle	750= 750 LPF	750= 750 LPF	WW= Wall Wash	
	_x_L= L-Shape	1000= 1000 LPF	1000= 1000 LPF		
	_x_x_U= U-Shape	XXX= Custom LPF	XXX= Custom LPF		

CCT	CRI	FINISH	MOUNTING	VOLTAGE	ELECTRICAL
30K= 3000K	80= 80	STANDARD	CABLES WITH CANOPY KITS	U= 120-277	1C= Single Circuit
35K= 3500K	90= 90 (R9 50 min)	PW= Powder Coat White	ACW05= White Cord 5'	C= 347	2C= Separate D/I Circuits
40K= 4000K		PB= Powder Coat Black	ACW10= White Cord 10'		(separate control of direct and indirect)
50K= 5000K		PS= Powder Coat Silver	ACB05= Black Cord 5'		MC= Multiple Circuits
TW= Tunable white ¹ (2700-6500K)			ACB10= Black Cord 10'		(multiple switch legs across run length)
		PREMIUM	CABLES WITH LOOPS		EC= Emergency Circuit
		RALxxx= Powder Coat RAL xxxx (Gloss Finish)	ALW10= White Cord 10'		(separate power drops for EC fixtures)
		PSFx= Prem Stock Finish	ALB10= Black Cord 10'		GTD= Generator Transfer Device
		CUSTOM	WALL MOUNTS		
		PO= Powder Other	WM= Wall Mount		
			AWM= Architectural Wall Mt		
		See pg. 8 for standard and premium options.	EWMexx= Extruded Wall Mount, xx"		
			STEM WITH CANOPY KITS		
			STEMWxx= Stem White, xx"		
			STEMBxx= Stem Black, xx"		

OPTIONS

SPECIALTY DRIVERS (Standard driver is 0-10V, dim to 1% output current)

DT1=eldoLED EcoDrive Dim to 1% (0-10V)
DT2=eldoLED SoloDrive Dim to 0.1% (0-10V)
PSRD=Philips Sensor Ready (DALI) Driver
LDE1=Lutron Hi-Lume EcoSystem LED driver with Soft-on, Fade-to-Black
TW-A=Tunable White, 0-10v²
TW-EL=eldoLED DUALdrive Tunable White (DALI)²
LD2=Lutron DALI 2 Digital Tunable White driver with 1% dimming²
RD-xx'-xxxx= Remote Driver 120V-277V
 Consult Factory

SENSORS

DMxx%=Daylight/Motion Sensor (xx%=% Min. Dimming)
VDO=Lutron Vive Integral fixture control (RF w/ daylight and occupancy)
AWNR-W=Lutron Athena Wireless Node (RF only)³ - White Finish
AWNR-B= Lutron Athena Wireless Node (RF only)³ - Black Finish
AWNS-W= Lutron Athena Wireless Node with Sensor - White Finish
AWNS-B= Lutron Athena Wireless Node with Sensor - Black Finish
NLA= Acuity nLight Air
WVL= Cooper Wavelinx

BATTERIES

#EMB6=6W EM Battery (Iota/Bodine)
#EMB10=10W EM Battery (Iota/Bodine)
#FCEMB10= 10W EM Battery (Factory Choice)
#FCEMB14= 14W EM Battery (Factory Choice)

¹ Tunable White Driver must be specified in options


² 50 Watt Max. Dual driver required for higher fixture wattage

³ D4i driver for static & DALI-2 Type 8 for tunable.


EXAMPLE: TALLDI-40-500-750-WD-BW-35K-90-PW-ACW10-U-1C-1EMB10

MOUNTING OPTIONS


ACxxx (Aircraft Cable with Canopy) - Drywall, Solid, Tile (On-Grid), Tile (Off-Grid)




ALxxx (Aircraft Cable with Loops)



AWM (Architectural Wall Mount)






WM (Wall Mount)





MOUNTING OPTIONS, CONTINUED

EWM (Extruded Wall Mount)

*Note: 3" standard EWM, custom sizes available up to 12"



STEMWxx, STEMBxx (Stem Mount)



ROW CONFIGURATIONS

xx (Run Length)

The standard construction of run lengths follows the logic of the table below. Consult factory for additional information.

Run lengths always start with the longest fixture and receives the power feed.

# of Sections	Total Length																																						
	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
2	1																																						
3		1																																					
4			1					1	1	1	1					1	1	1	1						1	1	1	1					1	1	1	1			
5				1				1			1				1				1						1				1				1				1		
6					1			1			1				1				1					1				1				1				1			
7						1			1			1			1				1					1				1				1				1			
8						1			1	1	1	1	2	1	1	1	2	2	2	2	3	2	2	2	3	3	3	3	4	3	3	3	4	4	4	4			

NOTE: Fixtures in continuous runs are available in 6" increments. Consult factory for smaller increments.

Sxx (Symmetric Run)

The construction of Sxx (y') is to build with equal length fixtures. The xx indicates the run length. The y' indicates the fixture length used to create the run. Please indicate this on your P.O. when placing your order.

S12 (2')	2'	2'	2'	2'	2'
S12 (3')	3'	3'	3'	3'	3'
S12 (4')	4'	4'	4'	4'	4'
S12 (6')	6'	6'	6'	6'	6'

MOUNTING LOCATIONS

Each starter or individual fixture will be provided with (2) mounting supports (●). Each additional fixture will be provided with (1) support which can be located anywhere along the 2nd half of the fixture (highlighted below):


Examples of continuous run mounting locations are as follows:

12' RUN	●	8'	●	4'	
16' RUN	●	8'	●	8'	
20' RUN	●	8'	●	8'	4'
24' RUN	●	8'	●	8'	8'
28' RUN	●	8'	●	8'	8' 4'

TALL BEAM DIRECT/INDIRECT

JOINT SHAPE CONFIGURATION WITH MITER CUTS




We provide joint configurations in the stock size of 24" X 24" as shown below.



<u>_x_RECT</u>
Rectangle
Supply AxB dimensions

<u>_x_L</u>
L-Shape
Supply AxB dimensions

<u>_x_x_U</u>
U-Shape
Supply AxBxC dimensions




● = Power Location

TALL BEAM DIRECT/INDIRECT

PERFORMANCE


WIDE DIFFUSE / BATWING - 325 DIRECT/750 INDIRECT (80+ CRI)



Model	Lumens	Watts	LPW
TALLDI-4-325-750-WD-BW-30K	4300	37	116
TALLDI-4-325-750-WD-BW-35K	4300	36	120
TALLDI-4-325-750-WD-BW-40K	4300	35	124
TALLDI-4-325-750-WD-BW-50K	4300	34	126

Model	Lumens	Watts	LPW
TALLDI-8-325-750-WD-BW-30K	8600	72	119
TALLDI-8-325-750-WD-BW-35K	8600	71	121
TALLDI-8-325-750-WD-BW-40K	8600	68	127
TALLDI-8-325-750-WD-BW-50K	8600	67	128

SATINICE DIFFUSE / CLEAR - 400 DIRECT/375 INDIRECT (80+ CRI)



Model	Lumens	Watts	LPW
TALLDI-4-400-375-SD-CL-30K	3,025	25	122
TALLDI-4-400-375-SD-CL-35K	3,025	24	128
TALLDI-4-400-375-SD-CL-40K	3,025	23	132
TALLDI-4-400-375-SD-CL-50K	3,025	23	134

Model	Lumens	Watts	LPW
TALLDI-8-400-375-SD-CL-30K	6,050	47	128
TALLDI-8-400-375-SD-CL-35K	6,050	45	134
TALLDI-8-400-375-SD-CL-40K	6,050	44	138
TALLDI-8-400-375-SD-CL-50K	6,050	43	141


TALL BEAM DIRECT/INDIRECT

FINISHES

STANDARD FINISHES



WHITE MINI TEXTURE



BLACK MINI TEXTURE




SILVER SPARKLE TEXTURE

PREMIUM STOCK FINISHES



PSF001 (WOOD#1)



PSF002 (WOOD#2)



PSF003 (WOOD#3)



PSF004 (WOOD#4)



PSF005 (WOOD#5)



PSF006 (WOOD#6)



PSF007 (STONE #1)



PSF008 (STONE #2)



PSF009 (METAL #1)

NOTE: A minimal impact to lead times will apply to products specified with Premium Stock Finishes (PSF). It is not to be assumed that these finishes are stocked in our warehouse, but rather, are readily available to us for your project.

All other custom finishes (PO) will incur a set up fee and will add an extended lead time to your project.

TALL BEAM DIRECT/INDIRECT

SPECIFICATIONS

Housing

Nominal 2" x 5." x .075" thick housing of continuous extruded 6063 T5 aluminum.

Color

Colors for the housing are available in a powder coated white, black, silver, and woodgrain with end cap to match. Consult factory for custom colors.

Luminaire Length

2', 4', 6' or 8' lengths are available for a single stand-alone section. Using internal joiners, these sections can be joined to form longer rows.

End Caps

Injection molded flat end caps are mechanically attached with no exposed fasteners to enhance architectural aesthetic and prevent light leak.

Source

Lumen packages are available in four color temperature options (3000K, 3500K, 4000K and 5000K) — all within 3 MacAdam ellipses.

Certification

Intertek cETLus Listed. RoHS (Restriction of Hazardous Substances) and Buy American Act compliant.

Battery

Lithium ion battery providing up to 780lm(6W) or up to 1300lm(10W) for 90 minutes. UL924 listed. Class 2 compliant. Meets Title 20 CEC (California Energy Commission) efficiency standards.

Environment

Suitable for dry and damp locations.

Operating temp.: -40°C to +50°C

-40°F to +122°F

Dimming Driver (Integral Driver)

Constant current programmable LED driver. UL listed, class P, 0-10V, dim to 1% of output current. 2.5KV ring wave surge protection and >.90 power factor.


Packaging

Sustainably manufactured outside cardboard box and biodegradable, protective poly-foam luminaire inserts.


CONTROL

Sensor

Wattstopper FS-205 v2 Low Voltage PIR. Integrated photosensor for hold-off daylighting control. 24VDC operating voltage. Adjustable time delay (30 seconds to 30 minutes).



Wireless Node



WARRANTY

5-year limited warranty. Complete warranty terms can be located at:

http://www.starteklightingamerica.com/images/pdf/warranty/Beam_Series_Warranty.pdf

Note: Actual performance may differ as a result of installation environment and final application.

All values are design or typical values, measured under laboratory conditions, at 25°C (77°F).

COMPANION PRODUCTS

Tall Beam Direct

